

Pushbutton Shields for Series C100, D200W, H2200, J300, W100 and WC1500 Switches





FEATURES

- Protection against accidental actuation
- Rugged construction
- Anodized for corrosion protection
- Threaded or unthreaded
- Available in black, clear or red
- Various size ranges

DESCRIPTION

These anodized aluminum shields guard pushbuttons against accidental operation. Internally threaded and unthreaded, the shields are usually used on basic switches in place of mounting adapters, although Type W or other narrow adapters can be used with shields. Consult switch and adapter drawings for proper thread size when ordering shields. Order shields separately by part number.

SELECTION TABLE

	Type	Active P/N	Obsolete P/N	Color	Dimension "A"	Dimension "B"	Dimension "C"	Dimension "D"	Dimension "E"	
 	Knurled Shields	73-2474	120011	Clear Anodized	.625"	.875"	.500"	1/2-32 NS-2B	—	
		73-2474-2	102012	Black Anodized	.625"	.875"	.500"	1/2-32 NS-2B	—	
		73-2474-3	102012	Red Anodized	.625"	.875"	.500"	1/2-32 NS-2B	—	
		73-2475	120016	Clear Anodized	.406"	.875"	.281"	1/2-32 NS-2B	—	
		73-2475-2	120017	Black Anodized	.406"	.875"	.281"	1/2-32 NS-2B	—	
		73-2475-3	120018	Red Anodized	.406"	.875"	.281"	1/2-32 NS-2B	—	
	Knurled Shields	73-2486	120081	Clear Anodized	.406"	.875"	.281"	5/8-24 NEF-2B	—	
		73-2486-2	120082	Black Anodized	.406"	.875"	.281"	5/8-24 NEF-2B	—	
		73-2486-3	120083	Red Anodized	.406"	.875"	.281"	5/8-24 NEF-2B	—	
		73-2487	120091	Clear Anodized	.406"	.875"	.281"	15/32-32 NS-2B	—	
		73-2487-2	120092	Black Anodized	.406"	.875"	.281"	15/32-32 NS-2B	—	
		73-2487-3	120093	Red Anodized	.406"	.875"	.281"	15/32-32 NS-2B	—	
		Smooth Shields	73-2478	120031	Clear Anodized	.688"	.957"	.641"	1/2" HOLE	—
			73-2478-2	120032	Black Anodized	.688"	.957"	.641"	1/2" HOLE	—
73-2478-3	120033		Red Anodized	.688"	.957"	.641"	1/2" HOLE	—		
Smooth Shields	73-2479		120036	Clear Anodized	.844"	.957"	.719"	5/8-24 NEF-28	—	
	73-2479-2		120037	Black Anodized	.844"	.957"	.719"	5/8-24 NEF-28	—	
	73-2479-3		120038	Red Anodized	.844"	.957"	.719"	5/8-24 NEF-28	—	
 	Rollo Edge Shields	73-2476	120021	Clear Anodized	.422"	1.063"	.375"	1/2" HOLE	61/64	
		73-2476-2	120022	Black Anodized	.422"	1.063"	.375"	1/2" HOLE	61/64	
		73-2476-3	120023	Red Anodized	.422"	1.063"	.375"	1/2" HOLE	61/64	
		73-2477	120026	Clear Anodized	.688"	1.063"	.641"	1/2" HOLE	61/64	
		73-2477-2	120027	Black Anodized	.688"	1.063"	.641"	1/2" HOLE	61/64	
		73-2477-3	120028	Red Anodized	.688"	1.063"	.641"	1/2" HOLE	61/64	
		73-2480	120041	Clear Anodized	.422"	1.063"	.375"	5/8" HOLE	61/64	
		73-2480-2	120042	Black Anodized	.422"	1.063"	.375"	5/8" HOLE	61/64	
		73-2480-3	120043	Red Anodized	.422"	1.063"	.375"	5/8" HOLE	61/64	
		73-2481	120046	Clear Anodized	.610"	1.188"	.563"	5/8" HOLE	1 3/32	
		73-2481-3	120048	Red Anodized	.610"	1.188"	.563"	5/8" HOLE	1 3/32	
		73-2485	120071	Clear Anodized	.688"	1.063"	.641"	5/8" HOLE	61/64	
		73-2485-2	120072	Black Anodized	.688"	1.063"	.641"	5/8" HOLE	61/64	
		73-2485-3	120073	Red Anodized	.688"	1.063"	.641"	5/8" HOLE	61/64	
	Rollo Edge Shields	73-2488	120106	Clear Anodized	.500"	1.063"	.375"	5/8-24 NEF-2B	61/64	
		73-2488-2	120107	Black Anodized	.500"	1.063"	.375"	5/8-24 NEF-2B	61/64	
		73-2488-3	120108	Red Anodized	.500"	1.063"	.375"	5/8-24 NEF-2B	61/64	
		73-2489-2⓪	120127	Clear Anodized	.719"	1.063"	.594"	5/8-24 NEF-2B	61/64	
		73-2489-3⓪	120128	Black Anodized	.719"	1.063"	.594"	5/8-24 NEF-2B	61/64	
		73-2489-4⓪	120129	Red Anodized	.719"	1.063"	.594"	5/8-24 NEF-2B	61/64	
		73-2490	120146	Clear Anodized	.547"	1.063"	.500"	5/8" HOLE	61/64	
		73-2490-2	120147	Red Anodized	.547"	1.063"	.500"	5/8" HOLE	61/64	
		73-2490-3	120148	Black Anodized	.547"	1.063"	.500"	5/8" HOLE	61/64	

⓪ May also be used with following mounting adapter types: A, B, D, DA, E, HA, P, PA, U, W.