

Series T and TW

T 2150, TW 20,000, T 2660, TW 20,001

Series T

SPECIFICATIONS

- Seal: Dust resistant
- Type of Operation: Maintained
- Electrical Life: 10,000 operations at 28VDC or 115VAC
- Mechanical Life: 20,000 operations
- Operating Temp. Range: -85°F to +160°F (-65°C to +71°C)

CURRENT RATINGS

| Catalog Number | Poles and Throw | 28VDC | | | 115 VAC | | |
|----------------|-----------------|------------------|-----------------------|-----------------------|-----------|-----------------------|-----------------------------|
| | | Lamp Load (Amps) | Resistive Load (Amps) | Inductive Load (Amps) | Lamp Load | Resistive Load (Amps) | Inductive Load (Amps) (.75) |
| T1002 | 1 P.S.T. | 5 | 20 | 15 | 3 | 10 | 10 |
| T1003 | 1 P.D.T. | 5 | 20 | 15 | 3 | 10 | 10 |
| T2106 | 1 P.D.T.* | — | 10 | 5 | — | 10 | 5 |
| T2114 | 1 P.D.T.* | — | 10 | 5 | — | 10 | 5 |
| T2150 | 2 P.D.T. | — | 3 | 1 | — | 3 | 1 |
| T2153 | 2 P.D.T. | — | 3 | 1 | — | 3 | 1 |
| T3103 | 1 P.D.T. | — | 5 | 3 | — | 5 | 3 |
| T3113 | 1 P.D.T. | — | 5 | 3 | — | 5 | 3 |

*Two Circuit



T2114



T2153



T3113

Series TW (Sealed)

SPECIFICATIONS

- Seal: Dust proof (per MIL-S-83731)
- Type of Operation: Maintained
- Electrical Life: 20,000 operations at 28VDC or 115VAC
- Mechanical Life: 40,000 operations
- Operating Temp. Range: -40°F to +160°F (-40°C to +71°C)

CURRENT RATINGS

| Catalog Number | MS Number ^① | Poles and Throw | 28VDC | | | 115 VAC | | |
|----------------|------------------------|-----------------|-----------|----------------|----------------|-----------|----------------|-----------------------|
| | | | Lamp Load | Resistive Load | Inductive Load | Lamp Load | Resistive Load | Inductive Load (Amps) |
| TW1002 | — | 1 P.S.T. | 5 | 20 | 15 | 3 | 10 | 10 |
| TW1003 | — | 1 P.D.T. | 5 | 20 | 15 | 3 | 10 | 10 |
| TW20000 | — | 2 P.D.T. | .5* | 2 | .5* | .1 | .1 | .1 |
| TW20001 | — | 1 P.D.T.* | .5 | 2 | .5 | .1 | .1 | .1 |
| TW20002 | MS18151-1 | 1 P.D.T. | .5 | 1 | .5 | .1 | .1 | .1 |

^① Qualified to MIL-S-83731

*Two Circuit



TW20000



TW20002



TW20001



TW1003

NOTE: For specific drawing dimensions, contact factory at 1-800-955-7354.